



General notes:

1. No part of this drawing must be scaled.
2. All dimensions should be checked before any work on the site commence.
3. Any discrepancies that may occur during the construction phase of this drawing must be brought immediately under the attention of the Engineer.

Construction notes:

1. Concrete Strength:
  - All concrete strengths to be 25MPa.
2. This drawing to be read in conjunction with relevant architect's drawings.
3. For setting out and final dimensions refer to architect's drawings.
4. Cover to reinforcement unless otherwise shown:
  - Beams & Slabs : 25mm
  - Columns : 25mm
  - Foundations : 50mm
5. All load-bearing brickwork to be plastered smooth and to receive 2 layers DPC prior to casting of concrete.
6. Foundations to be inspected by engineer prior to casting of any concrete.
7. Final soffit levels of beams and slabs as per architect's instruction.
8. All reinforcement must be checked by engineer prior to casting of any concrete.
9. All laps for reinforcement to be 50x diameter of smaller bar.
10. Three test cube results (28 day test results) will be provided to the engineer for every batch (not more than 50 cubic meter of concrete) poured.

|    |            |            |         |
|----|------------|------------|---------|
|    |            |            |         |
| A  | 24/10/2018 | For Tender | TN      |
| No | Date       | Revision   | Initial |

PRIVATE BAG 5530  
OSHAKATI, 9000  
TELL: 065 229500  
FAX 065 220435

Designed: NM

Checked: NM

|        |    |
|--------|----|
| Drawn: | NM |
|--------|----|

Architect:

PRIVATE BAG 5530  
OSHAKATI, 5000  
TELL: 065 229500  
FAX 065 220435

Client:

Project:

PROPOSED NEW STORE FOR  
OSHAKATI TOWN COUNCIL  
TECHNICAL DEPARTMENT

Drawing Title:

## ROOF LAYOUT AND DETAILS

Date of Drawing: 24/10/2023

Scale: AS SHOWN

Drawing No.:

**STORE-S-03**

Revision

0

Copyright of this drawing reserved